



## Technical specifications

### Electrical operating data

Voltage	24 V
Power supply type	DC
Energy consumption	5.7 W
Power consumption	240 mA

Data provided by the manufacturer

### Wiring

Red wire	+
Blue wire	-

### Performance

Moisture resistance index	IP68
Maximum air flow rate	40 m <sup>3</sup> /h

Data provided by the manufacturer

### Compatibility

Not compatible with models of Lucernario aerante with "Open-Close" air intakes.

## Technical specifications

### Installation



User 1: From the inside, place the counter plate and mark the holes with a marker.



User 1: Drill the micro-perforated mesh next to the marks.



User 1: Insert the fan with the vent facing downwards and keep it pressed.



User 2: From the outside, insert the counter plate.



User 2: Screw the self-locking nuts with your fingers.



User 2: Tighten the nuts with the wrench.



Proceed with wiring.

Thank you for purchasing our *Lucernario aerante* accessories.

The product and the *Lucernario aerante*® brand are property of Bottega del ferro.  
Bottega del ferro reserves all rights to modify the characteristics of the products shown without prior notice.  
This document and all the others relating to the products *Lucernario aerante* and *Lucernario aerante INOX* are available on the websites [www.lucernarioaerante.it](http://www.lucernarioaerante.it) and [inox.lucernarioaerante.it](http://inox.lucernarioaerante.it).



Bottega del ferro  
Via del Boscone, 8  
25014 Castenedolo (BS) Italia  
T. +39 030 2731985  
F. +39 030 2130930  
[info@bottegadelferro.net](mailto:info@bottegadelferro.net)  
[www.bottegadelferro.net](http://www.bottegadelferro.net)  
[www.lucernarioaerante.it](http://www.lucernarioaerante.it)